

SUPER SAND - Especificaciones técnicas



Description

SUPER SAND es particularmente idóneo para los remolques que se utilizan en superficies arenosas y en condiciones climáticas cálidas. Este neumático se caracteriza por su elevada capacidad de flotación y es ideal para todas las operaciones que requieran un elevado nivel de manipulación.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Remolque

Version	STANDARD
Type	TT
Tyre Size	16.00 - 20

Dimensions International Standard

Ply Rating	16
Section Width (mm)	415
Overall Diameter (mm)	1305
Rim Rec	10.00 W

Load capacity (Kg)

km/h / bar	2.50
50	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 16:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..