

TERRA TRAX - Especificaciones técnicas



Description

TERRA TRAX ha sido específicamente desarrollado para las herramientas del forraje, siendo idóneo para las aplicaciones tanto por carretera como fuera de la carretera. TERRA TRAX asegura óptimas prestaciones en la carretera, un buen confort de conducción y una excelente auto-limpieza. La baja resistencia al rodamiento contribuye a reducir los consumos de carburante.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricultura: Maquinaria agrícola

Version	STANDARD
Type	TL
Tyre Size	400/45L - 17.5

Dimensions US Standard

Usa code	94063451
Ply Rating	14
Section Width (inch)	15.6
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	93.3
Rim Rec	14.00
ECE	E11-106R-006002

Load capacity (lbs)

mph / psi	87
25	8800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 7:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..