

TF 8181 - Especificaciones técnicas



Description

TF 8181 es un neumático que se utiliza tanto en el campo como en la carretera para los tractores 2WD/2RM empleados en los trabajos del campo y de transporte. Este neumático asegura un excelente comportamiento de la dirección.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricultura: Tractor 2WD

Industrial: Remolque

Version	STANDARD
Type	TT
Tyre Size	11.00 - 16
LI/SS	114 A8

Dimensions US Standard

Usa code	94032761
Ply Rating	8
Section Width (inch)	12.8
Overall Diameter (inch)	38.2
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	115
Rim Rec	W 10 L
Rim Alt	W 8 ; W 8 L
ECE	E4-106R-002673
TRA Code	F2

Load capacity (lbs)

mph / psi	40
25	2600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 7:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..