

TR 117 - Especificaciones técnicas



Description

TR 117 es ideal para las operaciones de riego con pivote central. El especial dibujo de la banda de rodadura se traduce en una excelente tracción y extraordinarias propiedades de autolimpieza.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Equipo de riego a pivote

Version	STANDARD
Type	TL
Tyre Size	13.6 - 24
LI/SS	119 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	350
Overall Diameter (mm)	1187
Static Loaded Radius (mm)	541
Rolling Circumference (mm)	3591
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-004419
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.20	2.85
30	1360	---
CREEP	---	2565

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN)

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 6:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..