

TR 128 - Ficha técnica



Description

TR 128 ha sido particularmente proyectado para tractores compactos y cultivadores rotativos. El amplio y profundo diseño de los tacos y la mezcla particularmente resistente a los cortes asegura una vida prolongada del neumático. TR 128 se distingue por la máxima tracción en los terrenos húmedos.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Cultivador rotativo • Vehículo universal

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
180/85 D 12	STANDARD	94058129	63 A6	4	5 JA		6.5	24.1	11.6	72.7	TT	E11-106R-004821
180/85 D 12	STANDARD	94059256	72 A8	6	5 JA		6.5	24.1	11.3	72.7	TT	E11-106R-005207
5 - 12	STANDARD	94044887		4	4 JA		5	21.8	10.3	66.9	TT	E11-106R-003477
5 - 12	STANDARD	94055883	60 A8	6	4 JA		5	21.8	10.3	66.9	TT	E11-106R-005189
6.00 - 12	STANDARD	94044894	65 A8	4	4.00 E	4.00 E DT	6.3	25	11.7	75.8	TT	E11-106R-003478
6.00 - 12	STANDARD	94045242	72 A8	6	4.00 E	4.00 E DT	6.3	25	11.7	75.8	TT	E11-106R-003479
6.00 - 12	STANDARD	94060511	78 A8	8	4.00 E	4.00 E DT	6.3	25	11.7	75.8	TT	
7 - 14	STANDARD	94050345	92 A8	8	5 JA	5 J	6.8	27.2	12.7	82.1	TT	E11-106R-004093

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 13:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..