

TR 133 - Especificaciones técnicas



Description

TR 133 ha sido especialmente proyectado para los tractores que se utilizan en los trabajos del campo. Gracias a el número aumentado de los tacos, este neumático se caracteriza por su excelente tracción así como por las elevadas propiedades de auto limpieza. TR 133 garantiza un ciclo de vida prolongado del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	13.6 - 38 (14.00 - 38)
LI/SS	136 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	350
Overall Diameter (mm)	1580
Static Loaded Radius (mm)	735
Rolling Circumference (mm)	4843
SRI (mm)	750
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-003549
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.50
30	2240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 15:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..