

## TR 145 - Especificaciones técnicas



### Description

TR 145 ha sido especialmente desarrollado para los tractores pequeños. El particular dibujo de la banda de rodadura ofrece una excelente tracción, así como extraordinarias propiedades de auto limpieza. El amplio y profundo diseño de los tacos asegura una vida prolongada del neumático. TR 145 presenta una amplia área de contacto que proporciona un excelente confort de guía y buena estabilidad direccional.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Minitractor

|           |             |
|-----------|-------------|
| Version   | STANDARD    |
| Type      | TT          |
| Tyre Size | 160/90 - 12 |
| LI/SS     | 76 A6       |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 6               |
| Section Width (mm)         | 160             |
| Overall Diameter (mm)      | 631             |
| Static Loaded Radius (mm)  | 294             |
| Rolling Circumference (mm) | 1969            |
| Rim Rec                    | 4.00            |
| ECE                        | E11-106R-005854 |
| TRA Code                   | R1              |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 2.50 |
| 30         | 400  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 16:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..