

TR 173 - Especificaciones técnicas



Description

TR 173 es un neumático para los tractores idóneo para condiciones mojadas y lo arrozales. El particular dibujo de la banda de rodadura ofrece óptimas características de auto limpieza, así como una reducida compactación del terreno gracias a su amplia área de contacto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	13.6 - 26
LI/SS	116 A8

Dimensions US Standard

Usa code	94064137
Ply Rating	6
Section Width (inch)	13.6
Overall Diameter (inch)	49.4
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	149.1
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-003555
TRA Code	R1W

Load capacity (lbs)

mph / psi	22
25	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 9:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..