

TR 270 - Especificaciones técnicas



Description

TR 270 es un neumático para tractores, idóneo para utilizarlo en las labores del campo. Este neumático ha sido especialmente proyectado para ofrecer las máximas prestaciones en terrenos húmedos y mojados. En estas condiciones del terreno, a un neumático se le requiere que ofrezca un agarre superior, así como elevadas propiedades de auto limpieza. TR 270 satisface perfectamente todas estas características.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TT
Tyre Size	23.1 - 26
LI/SS	145 A8

Dimensions US Standard

Usa code	94027958
Ply Rating	10
Section Width (inch)	23.2
Overall Diameter (inch)	64.8
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	193.8
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003620
TRA Code	R2

Load capacity (lbs)

mph / psi	20
25	6400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 13:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..