

## TR 273 - Especificaciones técnicas



### Description

TR 273 es un neumático para tractores, idóneo para utilizarlo en las labores del campo. Este neumático ha sido especialmente proyectado para ofrecer máximas prestaciones en terrenos húmedos y mojados. En estas condiciones del terreno, a un neumático se le requiere que ofrezca un agarre superior, así como elevadas propiedades de auto limpieza. TR 273 satisface perfectamente todas estas características.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Tractor

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 14.9 - 24 |
| LI/SS     | 124 A8    |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94051410        |
| Ply Rating                   | 8               |
| Section Width (inch)         | 15              |
| Overall Diameter (inch)      | 51.6            |
| Static Loaded Radius (inch)  | 23.4            |
| Rolling Circumference (inch) | 159.2           |
| Rim Rec                      | W 13            |
| Rim Alt                      | W 12            |
| ECE                          | E11-106R-004514 |
| TRA Code                     | R2              |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 38   |
| 25        | 3530 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 13:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..