

TR 317 - Ficha técnica



Description

TR 317 es idóneo para las operaciones en los segmentos de municipalidad y para utilizarlo en las labores del campo realizadas para maquinaria agrícola, las zanjadoras y las máquinas para la recogida de fruta. El neumático TR 317 presenta una amplia área de contacto que proporciona un excelente agarre y una extraordinaria estabilidad en cualquier condición y óptimas propiedades de auto-limpieza.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Maquinaria agrícola • Máquina para la recogida de fruta • Zanjadora

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.50 - 8	HD	6	7.00 I - 55 ; I - 70 ; I - 90		215	450	198	1305	TL	
18 X 8.50 - 8	STANDARD	4	7.00 I - 55 ; I - 70 ; I - 90		215	450	198	1305	TL	E11-106R-003495

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 2:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..