

TR 360 - Ficha técnica



Description

TR 360 es idóneo para utilizarlo con maquinaria agrícola en el transporte dentro y fuera de la carretera y en las aplicaciones de los prados y la jardinería. El particular dibujo de la banda de rodadura, así como la estructura de la carcasa garantizan un prolongado ciclo de vida del neumático.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Maquinaria agrícola

SIZE	Version	USACode	LI/SS DRIVE WHEEL	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 7 - 8	STANDARD	94013104		6	5.5		7.1	18.1	8	52.5	TL	E4-106R-002184
240/70 - 15 (28X9.00 - 15)	STANDARD	94075416	115 A8	8	7.00 I	6 ½ K	9.3	29.1	0	0	TL	E11-106R-008778

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..