

TR 390 - Especificaciones técnicas



Description

TR 390 es un neumático agro-industrial, idóneo para las remolques que transportan la caña da azúcar y los compactadores. El neumático TR 390 se caracteriza por su elevada capacidad de carga y el aumento de la durabilidad. Su versión "dual bead HD", de doble talón HD, es particularmente idónea para los tractores industriales y las operaciones de transporte con remolques, mientras que la versión "dual bead HD special", de doble talón HD especial, es ideal para los trabajos más pesados.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricultura: Remolque
Industrial: Compactador

Version	DUAL BEAD HD
Type	TL
Tyre Size	23.1 - 26
LI/SS	157 A8

Dimensions US Standard

Usa code	94030675
Ply Rating	18
Section Width (inch)	23.4
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 20 B
ECE	E11-106R-004607
TRA Code	R3

Load capacity (lbs)

mph / psi	38
25	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 6:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..