

TR 678 IND - Especificaciones técnicas

Description

TR 678 IND ha sido particularmente desarrollado para las aplicaciones industriales. El robusto dibujo de los tacos garantiza una excelente tracción y auto-limpieza. La tenaz estructura de la carcasa se traduce en una elevada capacidad de carga, mientras que los cinturones de acero protegen el neumático contra los pinchazos y otros daños. TR 678 IND se caracteriza por una mezcla resistente a los cortes que garantiza, incluso en terrenos difíciles y en condiciones extremas, una excelente resistencia a los cortes y los desgarros.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Pala excavadora • Remolque

Version	DUAL BEAD
Type	TL
Tyre Size	600/40 - 22.5
LI/SS DRIVE WHEEL	157 A8
LI/SS FREE ROLLING	169 A8

Dimensions US Standard

Usa code	94065301
Section Width (inch)	24.2
Overall Diameter (inch)	42.7
Static Loaded Radius (inch)	19
Rolling Circumference (inch)	128.5
Rim Rec	AG 20.00
ECE	E11-106R-006973

Load capacity (lbs)

mph / psi	60
25 FR	12790
25 DW	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..