



TRAC FARM PLUS - Ficha técnica



Description

TRAC FARM PLUS es un neumático posterior para tractores particularmente proyectado para los trabajos del campo y las operaciones de transporte. Este neumático se distingue por una banda de rodadura más profunda con tacos de doble ángulo, con el fin de asegurar tanto una excelente tracción como una confortable conducción por carretera. El especial diseño de la banda de rodadura ofrece un mayor contacto y una mejor estabilidad, así como óptimas propiedades de auto-limpieza. TRAC FARM PLUS ha sido realizado con una mezcla superior de la banda de rodadura que optimiza la resistencia al desgaste y prolonga el ciclo de vida del neumático.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricultura: Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
12.4 - 28	STANDARD	R1	125 A6	12	W 11	W 9 ; W 10	320	1295	603	3899	TT	E11-106R-004526
13.6 - 28	STANDARD	R1	128 A6	12	W 12	W 11	365	1345	621	4088	TT	E11-106R-004527
14.9 - 28	STANDARD	R1	134 A6	12	W 13	W 12 ; W 11	390	1380	642	4179	TT	E11-106R-006811
16.9 - 28	STANDARD	R1	143 A6	12	W 15 L	W 14 L	440	1435	660	4298	TT	E11-106R-003627
16.9 - 30	STANDARD	R1	144 A6	12	W 15 L	W 14 L	440	1475	679	4466	TT	E11-106R-004529

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 20:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..