

TRAC GRADER + - Especificaciones técnicas



Description

TRAC GRADER + (G-2) es un neumático de telas cruzadas que se utiliza en las motoniveladoras y representa una excelente elección para los clientes que tienen en cuenta el presupuesto. Su durable carcasa ha sido proyectada para resistir a lo largo del tiempo. El dibujo con capacidad de auto limpieza de la banda de rodadura presenta una relación de tacos-espacio que proporciona una óptima tracción en cualquier condición. La versión "special" está realizada con una mezcla especial, resistente a los cortes y los desgarres.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Motoniveladora

Version	STANDARD
Type	TT
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94059751
Ply Rating	12
Overall Width (inch)	14.3
Overall Diameter (inch)	53.1
Static Loaded Radius (inch)	23.5
Rolling Circumference (inch)	157.1
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00 VA SDC; 10.00 WA SDC
TRA Code	G2
Tread Depth	32

Load capacity (lbs)

mph / psi	36
25	6800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 3:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..