

TRAC MASTER - Especificaciones técnicas



Description

TRAC MASTER es un neumático para las labores del campo, los prados y la jardinería, idóneo para los minitractores y la maquinaria agrícola. El dibujo de la banda de rodadura asegura, óptima protección de campo, excelente tracción y propiedades de auto-limpieza.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricultura: Maquinaria agrícola • Minitractor

Version	STANDARD
Type	TL
Tyre Size	33 X 15.50 - 15

Dimensions International Standard

Ply Rating	6
Section Width (mm)	404
Overall Diameter (mm)	865
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2526
Rim Rec	13 LB
ECE	E4-106R-002329

Load capacity (Kg)

km/h / bar	2.10
50	1370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 7:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..