



TUF LUG - Ficha técnica



Description

TUF LUG es idóneo para los remolques y las camionetas utilizadas para transportar. Este neumático ofrece una óptima tracción y una extraordinaria durabilidad, asegurando un prolongado ciclo de vida del producto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Camión ligero • Remolque
Industrial: Camión ligero • Remolque

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
7.50 - 16	STANDARD	94014309	12	6.00 G	5.50 F	8.5	32.7	TT
7.50 - 16	STANDARD	94014316	14	6.00 G	5.50 F	8.5	32.7	TT
7.50 - 16	STANDARD	94014323	16	6.00 G	5.50 F	8.5	32.7	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 6:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..