

XL GRIP (G3) - Especificaciones técnicas



Description

XL GRIP (G-3) es un neumático de telas cruzadas que se utiliza en las motoniveladoras. Ha sido desarrollado para minimizar el riesgo de cortes y perforaciones en las operaciones más pesadas de nivelación que requieran una extraordinaria tracción.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Motoniveladora

Version	STANDARD
Type	TT
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94062959
Ply Rating	16
Overall Width (inch)	14.4
Overall Diameter (inch)	53
Static Loaded Radius (inch)	24.3
Rolling Circumference (inch)	157.6
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G3
Tread Depth	38

Load capacity (lbs)

mph / psi	51
25	8050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 3:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..