

XL GRIP IND3 (ECH) - Especificaciones técnicas



Description

XL GRIP (IND-3) es un neumático de telas cruzadas que se utiliza en los equipos de manipulación de los contenedores vacíos en las aplicaciones de apilado y elevación. Este neumático se caracteriza por una robusta carcasa que asegura una durabilidad avanzada, así como una elevada estabilidad en la modalidad de levantamiento.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Manipulador de contenedores vacíos

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	510
Overall Diameter (mm)	1615
Static Loaded Radius (mm)	739
Rolling Circumference (mm)	4780
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND3

Load capacity (Kg)

km/h / bar	9.00
10	20250
25	18750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 15:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..