

XL GRIP IND3 (RTG) - Especificaciones técnicas



Description

XL GRIP (IND-3) es un neumático de telas cruzadas que se utiliza en las grúas RTG para las aplicaciones de apilado y elevación. Este neumático se caracteriza por una robusta carcasa realizada con una mezcla de la banda de rodadura específicamente formulada que asegura un ciclo de vida prolongado de lo neumático.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Grúa RTG

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	40
Overall Width (mm)	510
Overall Diameter (mm)	1615
Static Loaded Radius (mm)	739
Rolling Circumference (mm)	4780
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND3

Load capacity (Kg)

km/h / bar	10.00
10	22950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 5:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..