

XL GRIP (L3) - Especificaciones técnicas



Description

XL GRIP (E-3/L-3) es un neumático de telas cruzadas de base ancha (**wide**) desarrollado para palas cargadoras, que minimiza el riesgo de cortes y perforaciones en las operaciones de carga más pesadas. Este neumático asegura una excelente tracción, así como un ciclo de vida prolongado del producto.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Pala cargadora

OTR: Buldócer • Pala cargadora

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

Dimensions US Standard

Usa code	94015917
Ply Rating	28
Overall Width (inch)	29.9
Overall Diameter (inch)	73.2
Static Loaded Radius (inch)	33.4
Rolling Circumference (inch)	218.3
Rim Rec	25.00/3.5
TRA Code	L3
Tread Depth	49

Load capacity (lbs)

mph / psi	62
5	38600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 13:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..