

XL GRIP (SCRAPER) - Especificaciones técnicas



Description

XL GRIP (SCRAPER) es un neumático de base ancha no direccional para las mototraíllas en cualquier terreno. Este neumático se caracteriza por una robusta carcasa y una mezcla específicamente formulada que aseguran una excelente resistencia a los cortes y las laceraciones así como durabilidad y tracción excepcionales también en condiciones de trabajo pesadas. Otras ventajas son las extraordinarias propiedades de autolimpieza y optima estabilidad.

UM

US Standard

Construction

✚ BIAS

Machinery

OTR: Mototraílla

Version	STANDARD
Type	TL
Tyre Size	33.25 - 35

Dimensions US Standard

Usa code	94057429
Ply Rating	32
Overall Width (inch)	33.9
Overall Diameter (inch)	89.4
Rim Rec	27.00/3.5
Rim Alt	29.00/3.5
TRA Code	E3
Tread Depth	58

Load capacity (lbs)

mph / psi	47	65
30	35300	-
5	-	56800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 16:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..