

AGRI TRAILER - Fiche de données



Description

AGRI TRAILER a été spécialement conçu pour les remorques de tracteur. Ce pneu est idéal pour l'agriculture moderne du fait qu'il convient aussi bien pour les de transport en assurant un cycle de vie plus long sur route que hors route. Sa construction robuste se traduit par une capacité de charge élevée, tandis que sa bande de roulement extra-profonde lui permet de faire plus de kilomètres.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
10.00 - 20	STANDARD	18	7.5	7.0 ; 8.0	286	1080	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 13:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..