

AGRIMAX ELOS - Spécifications techniques



Description

AGRIMAX ELOS a été conçu pour assurer la plus grande traction même dans des conditions particulièrement difficiles sur terrains mouillés - tels les rizières - et marécageux. Le dessin de la bande de roulement a été élaboré spécialement pour garantir d'excellentes qualités d'auto-nettoyage, ce qui est fondamental lors des travaux dans les champs boueux et pendant les transferts. Pour optimiser la productivité de l'entreprise agricole, des bourrelets de protection sur les flancs ont été insérés dans le dessin du pneu AGRIMAX ELOS pour assurer à tout moment la plus grande protection contre d'éventuels dommages.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TL
Tyre Size	520/85 R 42 (20.8 R 42)
LI/SS	167A8/B

Dimensions US Standard

Usa code	94075850
Section Width (inch)	20.3
Overall Diameter (inch)	78.3
Static Loaded Radius (inch)	36.2
Rolling Circumference (inch)	240
Rim Rec	DW 16 L
Rim Alt	DD 18 L ; DW 18 L
ECE	E11-106R-0010146
TRA Code	R2

Load capacity (lbs)

mph / psi	14	17	20	23	29	35	41	46	52	58
30	4700	5530	6370	7100	7940	8650	9500	10460	11300	12010
25	4700	5530	6370	7100	7940	8650	9500	10460	11300	12010
20	5030	5920	6820	7590	8500	9270	10160	11200	12090	12860
5 LT	6280	7420	8540	9500	10640	11600	12730	14020	15140	16100
5 HT	5030	5920	6820	7590	8500	9270	10160	11200	12090	12860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 06:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..