

## AGRIMAX FORTIS - Spécifications techniques



### Description

AGRIMAX FORTIS est un partenaire fiable pour toutes vos opérations de préparation, plantation et traitement du terrain et les applications de transport. Conçu pour équiper les tracteurs plus puissants de la nouvelle génération, AGRIMAX FORTIS vous permet de transporter des charges très lourdes avec une vitesse jusqu'à 65 km/h. Le pneu se distingue par une manœuvrabilité et un confort excellent/s pour assurer une expérience extraordinaire de conduite. La carcasse renforcée en nylon garantit une productivité augmentée dans les champs en conservant le sol grâce au compactage réduit.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agriculture: Tracteur

|           |             |
|-----------|-------------|
| Version   | SPECIAL     |
| Type      | TL          |
| Tyre Size | 710/75 R 42 |
| LI/SS     | 175 D/172 E |

Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94050123       |
| Section Width (inch)         | 28.2           |
| Overall Diameter (inch)      | 84             |
| Static Loaded Radius (inch)  | 38.2           |
| Rolling Circumference (inch) | 252.2          |
| Rim Rec                      | DW 23 B        |
| Rim Alt                      | DW 25 B        |
| ECE                          | E4-106R-001835 |
| TRA Code                     | R1W            |

Load capacity (lbs)

| mph / psi | 9    | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 6670 | 7780  | 8750  | 9720  | 10700 | 11530 | 12790 | 13890 |
| 40        | 7310 | 8520  | 9590  | 10650 | 11720 | 12630 | 14000 | 15210 |
| 30        | 7670 | 8950  | 10060 | 11190 | 12300 | 13260 | 14700 | 15970 |
| 25        | 8000 | 9340  | 10500 | 11670 | 12840 | 13830 | 15340 | 16670 |
| 20        | 8400 | 9800  | 11020 | 12250 | 13470 | 14530 | 16100 | 17490 |
| 5 LT      | 9790 | 11420 | 12850 | 14270 | 15710 | 16930 | 18760 | 20390 |
| 5 HT      | 8400 | 9800  | 11020 | 12250 | 13470 | 14530 | 16100 | 17490 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..