

AGRIMAX RT 600 - Spécifications techniques

Description

AGRIMAX RT 600 est le pneu idéal pour les pelouses et les applications récolte et pulvérisation. Grâce à sa large zone de contact, AGRIMAX RT 600 garantit une répartition optimisée de la pression sur le terrain en réduisant les dommages sur les prairies et en protégeant le sol. Grâce à la technologie avec épaulement arrondi, la tringle renforcée et un nombre augmenté de crampons, ce pneu garantit une grande stabilité et une traction excellente.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Épandeur • Tracteur



Version	STANDARD
Type	TL
Tyre Size	710/70 R 38
LI/SS	178 D/181 A8

Dimensions US Standard

Usa code	94063420
Section Width (inch)	27.8
Overall Diameter (inch)	77.1
Static Loaded Radius (inch)	34.7
Rolling Circumference (inch)	233.3
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-006178

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
40	6450	7640	8760	9750	10910	11900	13060	14050	15380	16530
30	6780	7990	9200	10250	11460	12500	13720	14760	16150	17360
25	7100	8370	9640	10740	12000	13090	14370	15460	16920	18190
20	7420	8750	10090	11220	12550	13690	15020	16170	17690	19010
5 LT	8640	10200	11750	13070	14630	15960	17500	18840	20610	22160
5 HT	7420	8750	10090	11220	12550	13690	15020	16170	17690	19010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..