

## AGRIMAX RT 657 - Fiche de données



### Description

AGRIMAX RT 657 est le pneu idéal pour le travail aux champs et pour l'utilisation sur route; certaines tailles conviennent également pour les vendanges. Ce pneu assure un excellent confort de conduite ainsi que des économies de carburant non négligeables. Il se distingue de par une grande capacité de charge à de vitesses élevées. Agrimax RT 657 représente la meilleure solution pour ceux qui ont besoin d'un pneu polyvalent et fiable sans pour autant compromettre les performances.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agriculture: Tracteur • Machine à vendanger

| SIZE        | Version  | TRA Code | LI/SS        | RIM REC | RIM ALT       | SW  | OD   | SLR | RC   | SRI | Type | TKPH | ECE             |
|-------------|----------|----------|--------------|---------|---------------|-----|------|-----|------|-----|------|------|-----------------|
| 320/65 R 16 | STANDARD | R1W      | 117 D/120 A8 | W 10    | W 9 ; W 11    | 319 | 822  | 366 | 2466 | 390 | TL   |      | E4-106R-001815  |
| 320/65 R 18 | STANDARD | R1W      | 109 A8/B     | W 10    | W 9 ; W 11    | 319 | 873  | 392 | 2587 | 425 | TL   |      | E4-106R-000636  |
| 320/65 R 18 | STANDARD | R1W      | 125 A8/B     | W 10    | W 9 ; W 11    | 310 | 885  | 400 | 2667 | 400 | TL   |      | E11-106R-008145 |
| 340/65 R 18 | STANDARD | R1W      | 113 A8/B     | W 11    | W 10 ; W 12   | 343 | 899  | 400 | 2667 | 425 | TL   |      | E4-106R-001816  |
| 340/65 R 20 | STANDARD | R1W      | 124 D/127 A8 | W 11    | W 10 ; W 12   | 343 | 950  | 430 | 2892 | 450 | TL   |      | E4-106R-001413  |
| 420/65 R 20 | STANDARD | R1W      | 135 D/138 A8 | W 13    | W 11 ; W 12   | 418 | 1054 | 468 | 3162 | 500 | TL   |      | E4-106R-001390  |
| 440/65 R 20 | STANDARD | R1W      | 138 D/141 A8 | W 14 L  | W 13 ; W 15 L | 441 | 1080 | 479 | 3240 | 525 | TL   |      | E4-106R-000760  |
| 420/65 R 24 | STANDARD | R1W      | 138 D/141 A8 | W 13    | W 11 ; W 12   | 418 | 1156 | 519 | 3468 | 550 | TL   |      | E4-106R-000761  |
| 440/65 R 24 | SPECIAL  | R1W      | 135 D/138 A8 | W 14 L  | W 13 ; W 15 L | 441 | 1182 | 538 | 3546 | 575 | TL   |      | E4-106R-000616  |
| 440/65 R 24 | STANDARD | R1W      | 135 D/138 A8 | W 14 L  | W 13 ; W 15 L | 441 | 1182 | 538 | 3546 | 575 | TL   |      | E4-106R-000616  |
| 480/65 R 24 | SPECIAL  | R1W      | 140 D/143 A8 | W 15 L  | W 14 L        | 479 | 1234 | 562 | 3730 | 600 | TL   | 1    | E4-106R-000617  |
| 480/65 R 24 | STANDARD | R1W      | 140 D/143 A8 | W 15 L  | W 14 L        | 479 | 1234 | 562 | 3730 | 600 | TL   |      | E4-106R-000617  |
| 540/65 R 24 | SPECIAL  | R1W      | 146 D/149 A8 | W 16 L  | W 18 L        | 530 | 1312 | 590 | 3930 | 625 | TL   |      | E4-106R-000773  |
| 540/65 R 24 | STANDARD | R1W      | 146 D/149 A8 | W 16 L  | W 18 L        | 530 | 1312 | 590 | 3930 | 625 | TL   |      | E4-106R-000773  |
| 420/65 R 28 | STANDARD | R1W      | 135 D/138 A8 | W 13    | W 12 ; W 11   | 418 | 1257 | 584 | 3824 | 600 | TL   |      | E11-106R-002974 |
| 440/65 R 28 | STANDARD | R1W      | 138 D/141 A8 | W 14 L  | W 13 ; W 15 L | 441 | 1283 | 590 | 3927 | 625 | TL   |      | E4-106R-000767  |
| 480/65 R 28 | STANDARD | R1W      | 142 D/145 A8 | W 15 L  | W 14 L        | 479 | 1335 | 610 | 4091 | 650 | TL   |      | E4-106R-000653  |
| 540/65 R 28 | SPECIAL  | R1W      | 149 D/152 A8 | W 16 L  | W 18 L        | 530 | 1413 | 643 | 4253 | 675 | TL   |      | E4-106R-000650  |
| 540/65 R 28 | STANDARD | R1W      | 149 D/152 A8 | W 16 L  | W 18 L        | 530 | 1413 | 643 | 4253 | 675 | TL   |      | E4-106R-000650  |
| 600/65 R 28 | SPECIAL  | R1W      | 154 D/157 A8 | DW 20 B | W 18 L        | 611 | 1491 | 670 | 4470 | 700 | TL   |      | E4-106R-000621  |
| 600/65 R 28 | STANDARD | R1W      | 154 D/157 A8 | DW 20 B | W 18 L        | 611 | 1491 | 670 | 4470 | 700 | TL   |      | E4-106R-000621  |
| 420/65 R 30 | STANDARD | R1W      | 136 D/139 A8 | W 13    | W 12 ; W 11   | 418 | 1308 | 606 | 3952 | 625 | TL   |      | E11-106R-002975 |
| 540/65 R 30 | SPECIAL  | R1W      | 150 D/153 A8 | W 16 L  | W 18 L        | 530 | 1464 | 670 | 4403 | 700 | TL   |      | E4-106R-000651  |
| 540/65 R 30 | STANDARD | R1W      | 150 D/153 A8 | W 16 L  | W 18 L        | 530 | 1464 | 670 | 4403 | 700 | TL   |      | E4-106R-000651  |
| 600/65 R 30 | STANDARD | R1W      | 155 D/158 A8 | DW 20 B | W 18 L        | 611 | 1542 | 697 | 4609 | 725 | TL   |      | E4-106R-001825  |
| 540/65 R 34 | SPECIAL  | R1W      | 152 D/155 A8 | W 16 L  | W 18 L        | 530 | 1566 | 712 | 4742 | 750 | TL   | 1    | E4-106R-000652  |
| 540/65 R 34 | STANDARD | R1W      | 152 D/155 A8 | W 16 L  | W 18 L        | 530 | 1566 | 712 | 4742 | 750 | TL   |      | E4-106R-000652  |
| 600/65 R 34 | SPECIAL  | R1W      | 157 D/160 A8 | DW 20 B | W 18 L        | 611 | 1644 | 742 | 4960 | 775 | TL   | 1    | E4-106R-001405  |
| 600/65 R 34 | STANDARD | R1W      | 157 D/160 A8 | DW 20 B | W 18 L        | 611 | 1644 | 742 | 4960 | 775 | TL   |      | E4-106R-001405  |
| 540/65 R    | SPECIAL  | R1W      | 153 D/156    | W 16 L  | W 18 L        | 530 | 1667 | 760 | 5059 | 800 | TL   | 1    | E4-106R-000589  |

| 38          |              |     | A8           |         |                   |     |      |     |      |     |    |                 |
|-------------|--------------|-----|--------------|---------|-------------------|-----|------|-----|------|-----|----|-----------------|
| 540/65 R 38 | STANDARD     | R1W | 153 D/156 A8 | W 16 L  | W 18 L            | 530 | 1667 | 760 | 5059 | 800 | TL | E4-106R-000589  |
| 600/65 R 38 | SPECIAL      | R1W | 159 D/162 A8 | DW 20 B | W 18 L            | 611 | 1745 | 790 | 5247 | 825 | TL | E4-106R-000623  |
| 600/65 R 38 | STANDARD     | R1W | 159 D/162 A8 | DW 20 B | W 18 L            | 611 | 1745 | 790 | 5247 | 825 | TL | E4-106R-000623  |
| 650/65 R 38 | SPECIAL      | R1W | 163 D/166 A8 | DW 20 B | DW 21 B ; DW 23 B | 645 | 1811 | 830 | 5483 | 875 | TL | E4-106R-000624  |
| 650/65 R 38 | STANDARD     | R1W | 163 D/166 A8 | DW 20 B | DW 21 B ; DW 23 B | 645 | 1811 | 830 | 5483 | 875 | TL | E4-106R-000624  |
| 650/65 R 38 | STEEL BELTED | R1W | 178 A8/175 B | DW 20 B | DW 21 B ; DW 23 B | 645 | 1816 | 827 | 5488 | 875 | TL | E11-106R-008886 |
| 900/55 R 38 | STANDARD     | R1W | 179 D/181 A8 | DW 27 B | DW 30 B           | 880 | 1950 | 880 | 5842 | 925 | TL | E11-106R-006946 |
| 650/65 R 42 | STANDARD     | R1W | 165 D/168 A8 | DW 20 B | DW 21 B ; DW 23 B | 645 | 1913 | 878 | 5810 | 925 | TL | E4-106R-000625  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..