

## AGRIMAX TERIS - Fiche de données



### Description

Les moissonneuses-batteuses de grande puissance d'aujourd'hui demandent des pneus qui soient en mesure de supporter des engins et des charges lourdes sans endommager les cultures. BKT s'engage à vous offrir des solutions de pneus radiaux à l'avant-garde pour augmenter le rendement de votre récolte. AGRIMAX TERIS est le partenaire idéal pour vos opérations combinées. Il se distingue de par d'une excellente traction et d'une capacité de charge élevée en assurant les meilleures performances pour toutes les opérations de la récolte. La protection particulière du flanc et l'épaule renforcée augment la résistance – et donc un cycle de vie plus long du pneu – aussi dans les conditions pénibles, même en présence de chaumes acérés.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agriculture: Machine à récolter le coton • Moissonneuse

| SIZE                                | Version  | LI/SS        | RIM REC           | RIM ALT                                            | SW   | OD   | SLR | RC   | SRI | Type | ECE              |
|-------------------------------------|----------|--------------|-------------------|----------------------------------------------------|------|------|-----|------|-----|------|------------------|
| <b>620/75 R 26 CHO</b>              | STANDARD | 166 A8/B     | DW 20 B           |                                                    | 625  | 1590 | 730 | 4851 | 750 | TL   | E4-106R-001419   |
| <b>750/65 R 26 CHO (28L R 26)</b>   | STANDARD | 171 A8/B     | DW 25 B           | DW 23 B                                            | 764  | 1636 | 713 | 4908 | 750 | TL   | E4-106R-001496   |
| <b>750/65 R 26 CHO (28L R 26)</b>   | STANDARD | 166 A8/B     | DW 25 B           | DW 23 B                                            | 764  | 1636 | 713 | 4908 | 750 | TL   | E4-106R-000810   |
| <b>710/55 R 28 CHO</b>              | STANDARD | 164 A8/B     | DW 23 B           |                                                    | 716  | 1493 | 663 | 4442 | 700 | TL   | E11-106R-005940  |
| <b>620/75 R 30 CHO</b>              | STANDARD | 168 A8/B     | DW 20 B           |                                                    | 625  | 1692 | 779 | 5169 | 800 | TL   | E4-106R-001420   |
| <b>1050/50 R 32 CHO</b>             | HD       | 184 A8/181 B | 36.0 VA           |                                                    | 1059 | 1893 | 840 | 5685 | 875 | TL   | E11-106R-0010258 |
| <b>1050/50 R 32 CHO</b>             | STANDARD | 184 A8/181 B | 36.0 VA           |                                                    | 1059 | 1893 | 840 | 5685 | 875 | TL   | E4-106R-000813   |
| <b>650/75 R 32 CHO</b>              | STANDARD | 172 A8/B     | DW 21 B           | DW 20 B ; DW 23 B                                  | 670  | 1795 | 816 | 5378 | 850 | TL   | E4-106R-001425   |
| <b>800/65 R 32 CHO (30.5L R 32)</b> | STANDARD | 178 A8/175 B | DW 27 B           | DW 25 B ; DH 27 B                                  | 818  | 1853 | 838 | 5551 | 875 | TL   | E4-106R-001430   |
| <b>900/60 R 32 CHO</b>              | STANDARD | 185 A8/182 B | DW 27 B           | DW 28 B ; DW 30 B                                  | 875  | 1910 | 875 | 5775 | 900 | TL   | E4-106R-001433   |
| <b>900/60 R 32 CHO</b>              | STANDARD | 181 A8/178 B | DW 27 B           | DW 28 B ; DW 30 B                                  | 886  | 1910 | 854 | 5700 | 900 | TL   | E4-106R-001431   |
| <b>IF 710/75 R 32 CFO</b>           | STANDARD | 183 A8/B     | DW 25 B           | DW 23 B                                            | 716  | 1879 | 851 | 5653 | 875 | TL   | E11-106R-005025  |
| <b>IF 580/80 R 34 CFO</b>           | STANDARD | 177 D        | DW 20 B ; DW 20 A | DW 21 A ; DW 21 B                                  | 586  | 1792 | 810 | 5422 | 850 | TL   | E4-106R-001833   |
| <b>IF 710/75 R 34 CFO</b>           | STANDARD | 184 A8/B     | DW 25 B           |                                                    | 716  | 1930 | 870 | 5852 | 900 | TL   | E11-106R-004899  |
| <b>520/85 R 42</b>                  | STANDARD | 168 D        | DW 16 L           | W15L ; DW15L ; DD16L ; W16L ; DD18L ; DW18L ; W18L | 516  | 1951 | 890 | 5851 | 925 | TL   | E4-106R-001829   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..