

AGRIMAX TURF RT 333 - Spécifications techniques



Description

AGRIMAX TURF RT 333 (R-3+) est un pneu radial conçu pour les petits tracteurs utilisés dans le jardinage, les vignobles et les vergers. Sa conception à épaulement arrondi permet un faible compactage du sol et le rend extrêmement délicat sur le terrain. Sa bande de roulement extra-profonde (R-3+) et sa conception spéciale à blocs directionnels lui assurent une excellente traction dans les champs et sur la route, ainsi qu'une durée de vie prolongée du pneu. AGRIMAX TURF RT 333 (R-3+) dispose de grandes propriétés autonettoyantes et permet, grâce à sa faible résistance au roulement, de réaliser d'importantes économies de carburant.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur pour vergers • Micro tracteur •
Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	200/70 R 16
LI/SS	94 A8/B

Dimensions US Standard

Usa code	94074136
Section Width (inch)	7.9
Overall Diameter (inch)	27
Static Loaded Radius (inch)	12.5
Rolling Circumference (inch)	80.9
Rim Rec	W 6
ECE	E11-106R-008659
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	690	800	930	1040	1160	1280	1380	1480
25	690	800	930	1040	1160	1280	1380	1480
20	750	860	990	1110	1250	1370	1480	1590
5 LT	940	1080	1230	1390	1550	1710	1850	1980
5 HT	750	860	990	1110	1250	1370	1480	1590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..