

AGRIMAX TURF RT 333 - Spécifications techniques



Description

AGRIMAX TURF RT 333 (R-3+) est un pneu radial conçu pour les petits tracteurs utilisés dans le jardinage, les vignobles et les vergers. Sa conception à épaulement arrondi permet un faible compactage du sol et le rend extrêmement délicat sur le terrain. Sa bande de roulement extra-profonde (R-3+) et sa conception spéciale à blocs directionnels lui assurent une excellente traction dans les champs et sur la route, ainsi qu'une durée de vie prolongée du pneu. AGRIMAX TURF RT 333 (R-3+) dispose de grandes propriétés autonettoyantes et permet, grâce à sa faible résistance au roulement, de réaliser d'importantes économies de carburant.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Tracteur pour vergers • Micro tracteur •
Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	280/70 R 18
LI/SS	114 A8/114 B

Dimensions International Standard

Section Width (mm)	289
Overall Diameter (mm)	840
Static Loaded Radius (mm)	390
Rolling Circumference (mm)	2550
SRI (mm)	410
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E11-106R-006473

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	555	640	735	830	925	1015	1110	1180
40	555	640	735	830	925	1015	1110	1180
30	595	685	785	890	990	1090	1190	1265
10 LT	745	860	985	1110	1240	1365	1490	1585
10 HT	595	695	785	890	990	1090	1190	1265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..