



# AGRIMAX V-FLECTO - Spécifications techniques



## Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

## UM

International Standard

## Construction

RADIAL

## Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 480/80 R 38
LI/SS	166 D

## Dimensions International Standard

<b>Section Width (mm)</b>	479
<b>Overall Diameter (mm)</b>	1733
<b>Static Loaded Radius (mm)</b>	774
<b>Rolling Circumference (mm)</b>	5169
<b>SRI (mm)</b>	825
<b>Rim Rec</b>	DW 16 L
<b>Rim Alt</b>	DW 15 L
<b>ECE</b>	E11-106R-007168
<b>TRA Code</b>	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>70</b>	2270	2605	2990	3375	3760	4150	4535	4820
<b>From 65 to 40</b>	2495	2865	3290	3710	4135	4560	4985	5300
<b>30</b>	2545	2920	3355	3785	4220	4650	5085	5405
<b>20</b>	2590	2980	3420	3860	4300	4740	5180	5510
<b>10</b>	2745	3150	3615	4085	4550	5015	5485	5830
<b>*Upto 10 Cyc with front loader</b>	3490	4010	4605	5195	5790	6385	6975	7420
<b>10 HT</b>	2545	2830	3355	3785	4220	4650	5085	5405

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 13:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..