



# AGRIMAX V-FLECTO - Spécifications techniques



## Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

## UM

US Standard

## Construction

RADIAL

## Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 520/60 R 28 NRO
LI/SS	149 D

## Dimensions US Standard

<b>Usa code</b>	94060733
<b>Section Width (inch)</b>	20.3
<b>Overall Diameter (inch)</b>	52.6
<b>Static Loaded Radius (inch)</b>	23.1
<b>Rolling Circumference (inch)</b>	153.9
<b>Rim Rec</b>	DW 18 L
<b>Rim Alt</b>	W 18 L
<b>Narrow Rim option</b>	DW 16 L
<b>ECE</b>	E11-106R-005497
<b>TRA Code</b>	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
<b>45</b>	3570	4170	4750	5350	5920	6510
<b>from 40 to 25</b>	3940	4590	5220	5870	6510	7165
<b>20</b>	4010	4670	5320	5990	6640	7310
<b>12</b>	4090	4760	5420	6110	6770	7450
<b>5</b>	4320	5040	5740	6460	7160	7880
<b>*Upto 5 Cyc with front loader</b>	5500	6420	7310	8220	9120	10030
<b>5 HT</b>	4010	4670	5320	5990	6640	7310

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..