



## AGRIMAX V-FLECTO - Spécifications techniques



### Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 600/60 R 38 NRO
LI/SS	168 D

## Dimensions US Standard

<b>Usa code</b>	94065356
<b>Section Width (inch)</b>	23.1
<b>Overall Diameter (inch)</b>	66.3
<b>Static Loaded Radius (inch)</b>	29.8
<b>Rolling Circumference (inch)</b>	199.9
<b>Rim Rec</b>	DW 20 B
<b>Rim Alt</b>	DW 18 L
<b>Narrow Rim option</b>	DW 18 L
<b>ECE</b>	E11-106R-006414
<b>TRA Code</b>	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
<b>45</b>	5170	5960	6860	7640	8540	9330	10450	11230
<b>From 40 to 25</b>	5690	6550	7540	8400	9390	10250	11490	12350
<b>20</b>	5800	6680	7680	8560	9570	10450	11720	12590
<b>12</b>	5910	6800	7840	8730	9750	10660	11940	12830
<b>5</b>	6250	7200	8290	9240	10330	11280	12630	13580
<b>*Upto 5 Cyc with front loader</b>	7960	9170	10550	11760	13140	14350	16080	17280
<b>5 HT</b>	5800	6680	7680	8560	9570	10450	11720	12590

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 10:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..