



## AGRIMAX V-FLECTO - Spécifications techniques



### Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 600/65 R 34 NRO
LI/SS	169 D

## Dimensions US Standard

<b>Usa code</b>	94070275
<b>Section Width (inch)</b>	23.5
<b>Overall Diameter (inch)</b>	64.7
<b>Static Loaded Radius (inch)</b>	28.8
<b>Rolling Circumference (inch)</b>	195
<b>Rim Rec</b>	DW 21 B
<b>Rim Alt</b>	DW 20 B
<b>Narrow Rim option</b>	DW 18 L
<b>ECE</b>	E11-106R-007603
<b>TRA Code</b>	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
<b>45</b>	5360	6170	7100	7910	8840	9660	10820	11630
<b>From 40 to 25</b>	5890	6780	7800	8700	9720	10610	11890	12790
<b>20</b>	6010	6910	7960	8870	9920	10820	12140	13040
<b>12</b>	6120	7050	8110	9050	10110	11030	12370	13290
<b>5</b>	6470	7460	8590	9570	10690	11680	13080	14060
<b>*Upto 5 Cyc with front loader</b>	8240	9490	10920	12180	13610	14860	16650	17900
<b>5 HT</b>	6010	6910	7960	8870	9920	10820	12140	13040

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 14:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..