



# AGRIMAX V-FLECTO - Spécifications techniques



## Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

## UM

US Standard

## Construction

RADIAL

## Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 600/70 R 28
LI/SS	167 D

## Dimensions US Standard

<b>Usa code</b>	94074815
<b>Section Width (inch)</b>	23.7
<b>Overall Diameter (inch)</b>	61.1
<b>Static Loaded Radius (inch)</b>	26.1
<b>Rolling Circumference (inch)</b>	180
<b>Rim Rec</b>	DW 21 B
<b>Rim Alt</b>	DW 20 B
<b>ECE</b>	E11-106R-008814
<b>TRA Code</b>	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
<b>45</b>	5350	6220	7210	8080	8950	9820	10920
<b>From 40 to 25</b>	5890	6840	7930	8880	9840	10810	12010
<b>20</b>	6000	6980	8080	9060	10040	11010	12250
<b>12</b>	6120	7110	8230	9240	10240	11230	12490
<b>5</b>	6470	7530	8720	9780	10840	11890	13220
<b>*Upto 5 Cyc with front loader</b>	8230	9580	11100	12440	13790	15130	16820
<b>5 HT</b>	6000	6980	8080	9060	10040	11010	12250

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..