



# AGRIMAX V-FLECTO - Spécifications techniques



## Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

## UM

International Standard

## Construction

RADIAL

## Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 650/60 R 42
LI/SS	174 D

## Dimensions International Standard

<b>Section Width (mm)</b>	660
<b>Overall Diameter (mm)</b>	1845
<b>Static Loaded Radius (mm)</b>	834
<b>Rolling Circumference (mm)</b>	5564
<b>SRI (mm)</b>	875
<b>Rim Rec</b>	DW 23 B
<b>Rim Alt</b>	DW21B
<b>ECE</b>	E11-106R-008774

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>70</b>	2800	3230	3715	4140	4630	5055	5665	6095
<b>From 65 to 40</b>	3080	3550	4085	4555	5090	5560	6230	6700
<b>30</b>	3140	3615	4165	4640	5190	5665	6350	6830
<b>20</b>	3200	3690	4245	4735	5290	5780	6475	6965
<b>10</b>	3390	3905	4495	5010	5600	6115	6850	7370
<b>*Upto 10 Cyc with front loader</b>	4310	4970	5720	6375	7125	7785	8720	9380
<b>10 HT</b>	3140	3615	4165	4640	5190	5665	6350	6830

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..