



# AGRIMAX V-FLECTO - Spécifications techniques



## Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

## UM

US Standard

## Construction

RADIAL

## Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 710/55 R 38
LI/SS	175 D

## Dimensions US Standard

<b>Usa code</b>	94067107
<b>Section Width (inch)</b>	28
<b>Overall Diameter (inch)</b>	68.9
<b>Static Loaded Radius (inch)</b>	30.7
<b>Rolling Circumference (inch)</b>	206.4
<b>Rim Rec</b>	DW 25 B
<b>Rim Alt</b>	DW 24 B
<b>ECE</b>	E11-106R-006844
<b>TRA Code</b>	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
<b>45</b>	6370	7340	8440	9410	10520	11490	12870	13830
<b>from 40 to 25</b>	7000	8070	9280	10350	11560	12630	14150	15210
<b>20</b>	7140	8220	9470	10550	11790	12870	14430	15510
<b>12</b>	7290	8390	9660	10760	12030	13140	14720	15820
<b>5</b>	7700	8870	10210	11390	12720	13890	15560	16730
<b>*Upto 5 Cyc with front loader</b>	9800	11290	13000	14480	16190	17680	19810	21300
<b>5 HT</b>	7140	8220	9470	10550	11790	12870	14430	15510

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 11:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..