



# AGRIMAX V-FLECTO - Spécifications techniques



## Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

## UM

International Standard

## Construction

RADIAL

## Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 710/70 R 42
LI/SS	185 D

## Dimensions International Standard

<b>Section Width (mm)</b>	715
<b>Overall Diameter (mm)</b>	2061
<b>Static Loaded Radius (mm)</b>	921
<b>Rolling Circumference (mm)</b>	6182
<b>SRI (mm)</b>	975
<b>Rim Rec</b>	DW 25 B
<b>Rim Alt</b>	DW 23 B; DW 24 B
<b>ECE</b>	E11-106R-006266

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>70</b>	3960	4545	5220	5895	6565	7240	7915	8415
<b>From 65 to 40</b>	4350	4995	5735	6475	7215	7955	8695	9250
<b>30</b>	4435	5095	5850	6605	7360	8115	8870	9435
<b>20</b>	4525	5195	5965	6735	7505	8275	9045	9620
<b>10</b>	4785	5495	6310	8125	7940	8755	9565	10175
<b>*Upto 10 Cyc with front loader</b>	6090	6995	8030	9065	10105	11140	12175	12950
<b>10 HT</b>	4435	5095	5850	6605	7360	8115	8870	9435

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 13:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..