



# AGRIMAX V-FLECTO - Spécifications techniques



## Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

## UM

International Standard

## Construction

RADIAL

## Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 710/75 R 38
LI/SS	183 D

## Dimensions International Standard

<b>Section Width (mm)</b>	720
<b>Overall Diameter (mm)</b>	2060
<b>Static Loaded Radius (mm)</b>	905
<b>Rolling Circumference (mm)</b>	6151
<b>SRI (mm)</b>	950
<b>Rim Rec</b>	DW 24 B
<b>Rim Alt</b>	DW 23 B ; DW 25 B
<b>ECE</b>	E11-106R-006764
<b>TRA Code</b>	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
<b>70</b>	3980	4615	5255	5965	6605	7240	7960
<b>from 65 to 40</b>	4375	5075	5775	6560	7260	7960	8750
<b>30</b>	4460	5175	5890	6690	7405	8115	8925
<b>20</b>	4550	5275	6005	6820	7550	8275	9100
<b>10</b>	4810	5580	6350	7215	7985	8755	9625
<b>*Upto 10 Cyc with front loader</b>	6125	7105	8085	9180	10160	11140	12250
<b>10 HT</b>	4460	5175	5890	6690	7405	8115	8925

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..