



## AGRIMAX V-FLECTO - Spécifications techniques



### Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 900/60 R 42 NRO
LI/SS	189 D

## Dimensions US Standard

<b>Usa code</b>	94065257
<b>Section Width (inch)</b>	35.4
<b>Overall Diameter (inch)</b>	84.3
<b>Static Loaded Radius (inch)</b>	36.9
<b>Rolling Circumference (inch)</b>	251.6
<b>Rim Rec</b>	DW 30B
<b>Narrow Rim option</b>	DW 28 B
<b>ECE</b>	E11-106R-006165

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
<b>45</b>	10120	11770	13620	15280	16930	15890	20660
<b>From 40 to 25</b>	11120	12940	14980	16800	18620	20440	22710
<b>20</b>	11340	13190	15280	17130	18980	20840	23160
<b>12</b>	11560	13450	15570	17460	19360	21250	23610
<b>5</b>	12220	14230	16470	18470	20470	22470	24980
<b>*Upto 5 Cyc with front loader</b>	15560	18110	20960	23510	26060	28600	31790
<b>5 HT</b>	11340	13190	15280	17130	18980	20840	23160

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..