



# AGRIMAX V-FLECTO - Spécifications techniques



## Description

AGRIMAX V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'autonettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

## UM

US Standard

## Construction

RADIAL

## Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 600/70 R 30 NRO
LI/SS	168 D

## Dimensions US Standard

<b>Usa code</b>	94064601
<b>Section Width (inch)</b>	23.7
<b>Overall Diameter (inch)</b>	63.1
<b>Static Loaded Radius (inch)</b>	27.6
<b>Rolling Circumference (inch)</b>	185.5
<b>Rim Rec</b>	DW 21 B
<b>Rim Alt</b>	DW 20 B
<b>Narrow Rim option</b>	DW 18 B
<b>ECE</b>	E11-106R-006162

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
<b>45</b>	5610	6500	7410	8420	9310	10220	11230
<b>From 40 to 25</b>	6170	7150	8150	9260	10240	11230	12350
<b>20</b>	6290	7290	8300	9440	10440	11450	12590
<b>12</b>	6420	7430	8470	9620	10650	11670	12830
<b>5</b>	6790	7860	8950	10180	11250	12350	13580
<b>*Upto 5 Cyc with front loader</b>	8640	10010	11400	12960	14330	15720	17280
<b>5 HT</b>	6290	7290	8300	9440	10440	11450	12590

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..