

AGRIMAX V-FLECTO - Spécifications techniques



Description

AGRIMA V-FLECTO est la réponse de BKT aux exigences complexes en termes de technologie et performance pour les tracteurs de forte puissance. Ce pneu est parfait pour les travaux des champs et les applications de transport grâce au compactage réduit du sol et les propriétés d'auto-nettoyage. Conçu avec la technologie VF innovante, AGRIMAX V-FLECTO supporte des charges lourdes avec une pression de gonflage plus basse à des grandes vitesses. Le pneu est marqué NRO (Option Jante Étroite), ceci vous permet d'utiliser une jante standard. BKT a conçu ce pneu avec une géométrie optimisée pour assurer un confort de conduite amélioré dans les champs et sur route ainsi qu'une consommation réduite de carburant.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	VF 710/60 R 38 NRO
LI/SS	171 D

Dimensions US Standard

Usa code	94058563
Section Width (inch)	27.9
Overall Diameter (inch)	71.7
Static Loaded Radius (inch)	31.3
Rolling Circumference (inch)	214.4
Rim Rec	DW 25 B
Rim Alt	DW 23 B
Narrow Rim option	DW 23 B
ECE	E11-106R-004520
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
45	6780	7890	8990	10110	11220	12330
from 40 to 25	7450	8670	9890	11110	12330	13560
20	7590	8840	10070	11330	12580	13820
12	7750	9020	10270	11550	12820	14100
5	8190	9530	10870	12210	13560	14910
*Upto 5 Cyc with front loader	10430	12140	13830	15550	17260	18980
5 HT	7590	8840	10070	11330	12580	13820

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..