



AIROMAX AM 27 - Spécifications techniques



Description

AIROMAX AM 27 est un pneu pour une utilisation essentiellement sur route, idéal pour les applications sur grues dans le secteur bâtiment. Le pneu se distingue de par sa résistance à la chaleur et son confort exceptionnel. AIROMAX AM 27 est un pneu à haute vitesse particulièrement adapté pour toutes les opérations qui demandent un niveau de manœuvrabilité élevé.

UM

International Standard

Construction

RADIAL

Machinery

Industriel: Grue automotrice

Version	STANDARD
Type	TL
Tyre Size	385/95 R 25 (14.00 R 25)
LI/SS	170 F

Dimensions International Standard

Overall Width (mm)	372
Overall Diameter (mm)	1363
Static Loaded Radius (mm)	626
Rolling Circumference (mm)	4175
Rim Rec	10.00/1.5
ECE	E11-54R-0015911

Load capacity (Kg)

km/h / bar	9.00
80	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..