

AS 2001 - Spécifications techniques



Description

AS 2001 est un pneu diagonal à couches croisées, parfaitement adapté pour les tracteurs dans les opérations de travail de la terre et de transport. Le dessin particulier assure une excellente traction et des propriétés élevées d'auto-nettoyage. AS 2001 a été réalisé avec un mélange résistant à tous les types de coupure qui confère aussi une grande capacité de charge.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TL
Tyre Size	16.9 - 28
LI/SS	139 A8

Dimensions US Standard

Usa code	94030385
Ply Rating	12
Section Width (inch)	16.9
Overall Diameter (inch)	55.9
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	170
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E4-106R-002045
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..