

AS 504 - Spécifications techniques



Description

AS 504 est un pneu agro-industriel essentiellement conçu pour les opérations de travail de la terre, de manutention de matériaux et les outils agricoles. Ce pneu qui se distingue de par ses excellentes propriétés d'auto-nettoyage et par une adhérence améliorée, est idéal pour les remorques aux champs et les chargeurs télescopiques. AS 504 est disponible en différentes versions pour répondre aux exigences spécifiques de l'utilisateur : une version « HD » avec mélange particulièrement résistant aux coupures et déchirures, tandis que une version « spécial » avec une carcasse renforcée qui assure un cycle de vie plus long.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse télescopique • Remorque des champs

Industriel: Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	147 A8

Dimensions US Standard

Usa code	94019021
Ply Rating	10
Section Width (inch)	16.5
Overall Diameter (inch)	43.2
Static Loaded Radius (inch)	19.2
Rolling Circumference (inch)	126.5
Rim Rec	13
Rim Alt	12 SDC ; 14 ; 13 SDC
ECE	E4-106R-001875

Load capacity (lbs)

mph / psi	36
5 FR	9490
15 FR	8070
20 FR	7590
25 FR	6780
5 DW	6720
15 DW	5720
20 DW	5380
25 DW	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..