

AS 505 - Fiche de données



Description

AS 505 est parfaitement adapté pour le travail de la terre avec des remorques et des outils agricoles. Ce pneu se distingue de par ses excellentes propriétés d'auto-nettoyage et par une traction supérieure sur le terrain, notamment sur les sols boueux. Le pneu assure aussi un long cycle de vie.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Remorque

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
6.5/80 - 15	STANDARD	94019472	92 A8	104 A8	8	5.0	4½ K ; 5 K ; 5 J	6.7	27.4	12.8	82.9	TL	E4-106R-002660
6.5/80 - 15	STANDARD	94019465	86 A8	98 A8	6	5.0	4½ K ; 5 K ; 5 J	6.7	27.4	12.8	82.9	TL	E4-106R-002188

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..