



AS 507 - Fiche de données



Description

AS 507 a été conçu pour le travail de la terre avec des remorques et des outils agricoles. Ce pneu se distingue par ses excellentes propriétés d'auto-nettoyage et par une traction supérieure sur le terrain.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Outilage agricole • Remorque

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
185/65 - 15	STANDARD	76 A8	89 A8	4	5½ J		185	640	301	1894	TL	E4-106R-002185

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 10:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..