

AT 108 - Spécifications techniques



Description

AT 108 est un pneu pour tous les types de terrain pour les véhicules ATV/VTT. Le dessin de la bande de roulement assure des performances et du confort exceptionnels tant sur route qu'aux champs.

UM

US Standard

Construction



Machinery

Agriculture: Véhicule ATV

Version	STANDARD
Туре	TL
Tyre Size	AT 20 X 10 - 10

Dimensions US Standard

Usa code	94034499
Ply Rating	4
Section Width (inch)	9.8
Overall Diameter (inch)	20.2
Static Loaded Radius (inch)	9.3
Rolling Circumference (inch)	56.1
Rim Rec	8.0 AT
Rim Alt	7.5 AT; 8.5 AT
ECE	E11-75R-004567

Load capacity (lbs)

mph / psi	5
62	260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..