

AT 108 - Spécifications techniques



Description

AT 108 est un pneu pour tous les types de terrain pour les véhicules ATV/VTT. Le dessin de la bande de roulement assure des performances et du confort exceptionnels tant sur route qu'aux champs.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Véhicule ATV

Version	STANDARD
Type	TL
Tyre Size	AT 22 X 10 - 9

Dimensions International Standard

Ply Rating	4
Section Width (mm)	254
Overall Diameter (mm)	559
Rim Rec	8.0 AT
Rim Alt	7.5 AT ; 8.5 AT
ECE	E4-75R-0004982

Load capacity (Kg)

km/h / bar	0.35
100	136

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..